



sipdoor01
one button



sipdoor02
two button



sipdoor01C
one button
with LED and Camera



sipdoor02C
one button
with LED and Camera

IP Camera Intercom system

Door Entry Features:

- Backlit buttons
- Buttons dial an extension or group when pressed
- Two internal SPDT relays for controlling a door opener or light etc.
- Relays controlled individually by DTMF tones
- Multiple relay
- Volume control for speaker
- Gain control for microphone
- Camera permanently operational with MJPEG format
- LED illumination
- Support Day and Night mode
- Pop up Software to open door

Voice and Video:

- Session Initiation Protocol (SIP RFC3261)
- Registers to a SIP Registrar/SIP PBX
- Audio codecs supported: G711a, G711u, G726-32, GSM
- Video codecs supported: H.263, H.264
- Manual Echo Cancellation
- Symmetric RTP

Interface:

- 1x RJ45 LAN 10/100M
- 2x relay (NC,NO,COM)
- 1x 2pin (12V power adapter)

Networking:

- 10/100Mbps Ethernet connection
- DHCP or static IP
- Network-Time-Protocol
- HTTP management

Physical and Power:

- 185x99x40mm (HxWxD)
- Wall mountable
- Body material: anodized aluminum and ABS plastic
- 802.3af Power-over-Ethernet
- 12v DC or AC power supply
- 300mA Max consumption
- Max voltage of switch contact: 48V for I < 1A
- Max current of switch contact: 2A at V < 30 V
- Operating temperature: From - 20°C to + 70°C

IP-PBX Server Compatibility

Sip v2 IPPBX :

Asterisk, Elastix ,Trixbox, Cisco Call Manager, Alcatel Omni PCX, Avaya IPO, Sipdex IPPBX, Yeastar IPPBX, Zycoo IPPBX, Etc...

